US009411331B2

(12) **United States Patent**
Mitani et al.

(10) **Patent No.: US 9,411,331 B2**
(45) **Date of Patent: Aug. 9, 2016**

(54) **AUTOMATIC PROGRAMMING DEVICE AND METHOD**

(71) Applicants: **Yuka Mitani**, Tokyo (JP); **Kenji Iriguchi**, Tokyo (JP); **Sanae Chiba**, Tokyo (JP); **Yuji Fujimoto**, Aichi (JP)

(72) Inventors: **Yuka Mitani**, Tokyo (JP); **Kenji Iriguchi**, Tokyo (JP); **Sanae Chiba**, Tokyo (JP); **Yuji Fujimoto**, Aichi (JP)

(73) Assignee: **Mitsubishi Electric Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/421,311**

(22) PCT Filed: **Oct. 31, 2012**

(86) PCT No.: **PCT/JP2012/078223**
§ 371 (c)(1),
(2) Date: **Feb. 12, 2015**

(87) PCT Pub. No.: **WO2014/068715**
PCT Pub. Date: **May 8, 2014**

(65) **Prior Publication Data**

US 2015/0220079 A1 Aug. 6, 2015

(51) **Int. Cl.**
G06F 19/00 (2011.01)
G05B 19/4093 (2006.01)

(52) **U.S. Cl.**
CPC ***G05B 19/40937*** (2013.01); *G05B 2219/34088* (2013.01); *G05B 2219/35318* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G05B 19/40937; G05B 2219/35318; G05B 2219/35333; G05B 2219/35341; G05B 2219/34088; G05B 2219/45162; Y02P 90/265
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,249,135 A * 9/1993 Fujita G05B 19/40937 700/179
5,293,321 A * 3/1994 Fujita G05B 19/40935 700/182

(Continued)

FOREIGN PATENT DOCUMENTS

CN 102473009 A 5/2012
JP 06-210544 A 8/1994

(Continued)

OTHER PUBLICATIONS

Kaymakci, M., Z. M. Kilic, and Y. Altintas. "Unified cutting force model for turning, boring, drilling and milling operations." International Journal of Machine Tools and Manufacture 54 (2012): 34-45.*

(Continued)

Primary Examiner — Michael D Masinick
(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57) **ABSTRACT**

An automatic programming device includes: a machining-area-shape generation unit that generates machining-area shape data that is a machining area shape machined on the basis of machining-area data; and a chamfering tool-path generation unit that, when the machining area shape is a chamfering target part, generates chamfering tool-path data for chamfering according to chamfering data including the machining-area shape data, data on tool-to-be-used, and data on machining condition. When performing chamfering on a boundary of the shaped raw material and the machining area shape defined on a curved surface that is a shaped raw material, the chamfering tool-path generation unit generates a machining path, as the chamfering tool-path data, for realizing chamfering by using 2-axis machining of a rotating axis parallel to a central axis of the shaped raw material and with a linear axis parallel to a bottom surface of the machining area shape.

5 Claims, 15 Drawing Sheets